

STM STUDIO SUPPLIES *By professionals for professionals*

18 Dawson Street Naremburn NSW 2065 **T:** 02 9439 9060 **F:** 02 9439 9063 **E:** sales@stmstudiosupplies.com **W:** www.stmstudiosupplies.com

FIXED BARRES

available in

STM Studio Supplies have a range of wall mounting brackets each with their own advantages in practise and appearance.

Each can be matched with either a timber or metal barre and may be powder coated on request to any of the colours in the Dulux powder coating range. These colours can be viewed at www.duluxpowders.com.au Hardware for fixing is included but naturally no guarantees can be made on installation.

The prices as indicated are for 2.5 metre lengths for ease of freight and these may be joined at the support points if required. With both the timber barres and the aluminium we supply a joining system which allows shorter lengths to be seamlessly joined lessening freight costs and with no loss of user friendliness or strength. Lengths of up to 4.5 metres in timber and 6 metres in aluminium can be supplied on request.

With both the portable and fixed timber barres a strong and durable hardwood timber is finished to a satin gloss in hard wearing 2-pack epoxy.

- 2.5m powder coated aluminum barre - FP2.5 ●
- 2.5m anodised aluminum barre - FA2.5 ●
- 2.5m timber barre - FT2.5 ●

FIXING BRACKETS

options available



ANODISED ALUMINIUM
(strongest system we supply)

- 110mm offset - FBA ●

MASONRY BRACKET
wall bracket for brick and adjustable wall system

Painted Finish

- 16mm, 225mm offset - FBS ●

Powdercoated

- 16mm, 225mm offset - FBSP ●

STM STUDIO SUPPLIES *By professionals for professionals*

18 Dawson Street Naremburn NSW 2065 **T:** 02 9439 9060 **F:** 02 9439 9063 **E:** sales@stmstudiosupplies.com **W:** www.stmstudiosupplies.com

continued **FIXING BRACKETS**

options available

ROUND BRACKET

for gyprock or timber walls

Painted Finish

16mm, 225mm offset - FBR •

Powdercoated

- FBRP •



JOINERS

options available

ALUMINIUM

Snugly connects aluminium barres - JA •

TIMBER

Connecting system for timber barres - JT •



END SOCKETS


options available

ROUND SOCKET

This elegant round socket with secret fastening can only be used to secure one end - ESR •

SQUARE FLANGE

Allows fixing between walls or columns and is extremely robust - ESS •



STM STUDIO SUPPLIES *By professionals for professionals*

18 Dawson Street Naremburn NSW 2065 T: 02 9439 9060 F: 02 9439 9063 E: sales@stmstudiosupplies.com W: www.stmstudiosupplies.com

ADJUSTABLE WALL BRACKET SYSTEM

options available

Two brackets, height adjustable via large knobs, make for easy relocation of rail height on industrially rated track system - FWB •

COMPLETE SYSTEM

With 1x2.5x48mm aluminium barre - FWBA2.5 •

With 1x2.5x48mm timber barre - FWBT2.5 •



With a 245mm offset this system is unique in the world.

The adjustable wall bracket system allows barres up to 2.5m long to easily slide up and down a metre long 700kg rated tracking system to the desired height. It also allows the barre to be easily removed for storage. This leaves the studio free for other uses with only the slim track left unobtrusively on the wall (FWB).

Barres are available in timber (FWBT) and aluminium (FWBA). The aluminium may be powdercoated to taste (FWBP). Brackets may be either STM FBS at 225mm offset or FBA at 110mm offset to accommodate students of different size who may need to use the barre simultaneously (FWBAA and FWBTT).

This is an extraordinarily versatile system.

© Registered design.

STM STUDIO SUPPLIES *By professionals for professionals*

18 Dawson Street Naremburn NSW 2065 **T:** 02 9439 9060 **F:** 02 9439 9063 **E:** sales@stmstudiosupplies.com **W:** www.stmstudiosupplies.com

SECONDARY SCHOOL FACILITY STANDARD

options available

6 metre barre - EDS •



This "belt and braces" barre system conforms with the Education Facilities Research Group Specification Standard 406 Performance Workshop Exercise Barre, for Secondary Schools.

A 40mm NB 6mm pipe is supported off the wall at each end the Barre and a Standard 48.3mm timber Barre is offset 150mm from this with brackets at 1070mm. Support legs and brackets are then at evenly spaced intervals to a maximum of 1500mm along the steel main barre. Length may vary according to the requirements of a given room and for ease of transport this barre system is typically joined at 3metre modules.

Finished in a standard black powdercoat or you can choose any colour from the **Dulux Powdercoating Range** at no extra charge.